

**Specifications:**

1. High Performance Z80A CPU @ 4 MHz
2. 8 K Powerful Monitor FIRMWARE in 2764 Includes all standard Commands, Codes, Functions & Utility subroutines
3. 8 K user RAM
4. Memory expansion capability up to 40 K
5. Versatile Keyboard/Display controller using 8279
6. 48 Parallel I/O lines from two 8255 chips
7. Serial I/O through RS232 channel
8. Built-in audio cassette interface
9. 4 programmable counter timer channels from Z 80 CTC
10. Powerful Z80A interrupt capabilities
11. On-board EPROM programmer with ZIF socket for 2716 to 27512 EPROMs
12. 6 digit seven segment LED display
13. Highly reliable multi-function keypad with 24 keys
14. All address data and control lines buffered and brought out on 50 pin FRC connector
15. Supplied in a strong and attractive lightweight wooden case
16. Power supply : Specially designed 230 V AC Power supply

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in