



- Self contained trainers
- Each with 4 different Transducers
- Study of Transducer controlled switching / alarm systems
- On board signal conditioning circuitry
- Built-in DC power supply
- Functional blocks indicated on-board Mimics
- Fully documented Student Workbook and
- Operating Manual with each trainer

Experiments that can be performed

- Characteristics of IC temperature Sensor
- Characteristics of NTC Thermistor
- Characteristics of NTC Bridge Circuit
- Characteristics of Platinum RTD
- Characteristics of K type Thermocouple
- Temperature Controlled Alarm System

... and many more

Technical Specifications

Transducers : 4 Nos.

- N.T.C. Thermistor
- Platinum R.T.D.
- K Type Thermocouple
- IC Temperature Sensor

Heating Element : Wirewound resistance 47 Ω , 7

Signal Conditioning Circuitry :

- Instrumentation Amplifier
- X100 Amplifier
- DC Amplifier
- Comparator
- Electronic Switch

Input Circuits : Rotary & Slide Potentiometers

Output Circuits :

- Relay
- Buzzer

Interconnections : 4mm. banana sockets

Power Supply : 220 V \pm 10 %, 50 Hz / 60 Hz on request

Power Consumption : 2 VA (approx.)

Dimensions (mm) : W 340 \times D 240 \times H 105

Accessories : Line cord, Manual, Set of patch cords.

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in